



Progress on AST3-3 IR Camera Design

Jessica Zheng

Michael Ashley, Michael Burton, Vlad Churilov, Robert Content, Peter Gillingham, Karl Glazebrook, Lu Haiping, Mike Ireland, Jon Lawrence, Anna Moore, Jeremy Mould, Nick Staszak, Julia Time, Peter Tuthill, Lifang Wang, Xiangyan Yuan, Li Zhengyang, Yongtian Zhu



AST3-3 IR Camera and KISS

- AST3-NIR is version of AST3 dedicated to conduct the KISS infrared sky survey at Kdark.
- Technical concept developed during early 2014.
- China responsible for telescope hardware and control, logistics, deployment.
- Australia responsible for instrument hardware and control, and power generation system.
- AST3-3 telescope already funded and currently is at manufacturing. IR camera funded by Australian government LIEF grant 2014(PI:Jeremy Mould) .
- Project Kick-off meeting happened during 2015 International Collaboration Meeting on Antarctic Survey Telescopes (AST3), March, Hong Kong 2015.




Key parameters (thanks to Jeremy, Jon and Xiangyan)

Parameter	Value
λ ($\Delta\lambda$)	2.36 (0.18) μm (K_{dark})
Diameter	68cm
Image Quality	1.9'' (1.1 x diffraction limit)
Array	2048 x 2048, 18 μm pixels H2RG Teledyne preferred
Sampling	1''
Field of View	30' x 30'
<i>Achieving:</i>	
Background limited integration time	25 secs
1 σ 25 seconds	18.0 mags.
10 σ 1 hour	18.5 mags.
Saturation limit (in 25 sec)	$K_{\text{dark}} = 11.1$ mags.
With Background Sky [South Pole]	$K_{\text{dark}} = 17.0$ mags/arc ² =100 μJy /arc ²




AST3-3 IR Camera Preliminary Design







Optical design of IR camera



- Design has one asphere.
- Pixel size:
 - ✓ 18 μm .
 - ✓ 1.35" based on approximate calculations of size of total PSF including diffraction, as-designed aberrations, tolerances and seeing.
- Field:
 - ✓ 2048 x 2048 pixels.
 - ✓ 2765" x 2765".




IR camera Concept



- 1 – Detector assembly
- 2 – Optical Camera
- 3 – mirror
- 4 - Vacuum window
- 5 – Focusing Mechanism
- 6 – Cold Strap
- 7 – Cryocooler (Sunpower Stirling)
- 8 – Electronics Thermal Cabinet
- 9 – Vacuum vessel



AST3-3 IR Camera Layout




Overall Dimensions, approx: 700 x 500 x 300

Mass approx 30 kg



IR Camera on AST-3 telescope





Stray light and thermal analysis

- Scattering light analysis
- Thermal self emission


Surface property parameters(thanks to NIOAT)

material	absorptance	Specular Reflectance	Transmittance	BRDF A	BRDF B	BRDF g	Emissivity
mirror	0.03	0.956	0	0.00096	0.01	2	0.03
lens	0.001	0.015	0.984	0.00001	0.015	2	0.001
Tube/baffle	0.95	0.00001	0	0.0318	1	0	0.95
ITO	0.13	0.00187	0.85	0.0001	0.015	2	0.13

Point Source Transmittance

PST: Standard for stray light rejection evaluation.


$PST(\theta) = \text{focal plane irradiance} / \text{entrance aperture irradiance}(\theta)$






PST for IR camera

PST AST3-3_X direction




PST IR Camera_Y direction



Thermal self emission

Flooded Light from Detector Surface(Solid angle)




Three Temperature Zones:

- ✓ Zone1: Ambient temperature.
- ✓ Zone2: IR camera relay lens body.
- ✓ Zone3: Filter and FPA.




Thermal irradiance when the IR camera body painted with Acktar vacuum black



- Temperature Zones:
- ✓ Zone1: 198k-235K
 - ✓ Zone2: <160K
 - ✓ Zone3: 77K



Thermal Self Emission





AST3-3 IR camera Exposure time Calculator

AST3-3 IR Camera Exposure Time Calculator (V.0.1)

Target flux distribution

Object Magnitude: Observation Wavelength(um):

Target Geometry

☐ Point source ☐ Extended source:

CCD parameters

Pixel size: Dark Current: Read noise: Quantum Efficiency: Full Well Depth:

Sky conditions

Seeing: Sky Background: Mag: Jy

Instrument Setup

Filter Setup: Start Wavelength: Stop Wavelength: Ambient Temperature: Zenith Distance:

Signal to Noise Ratio(Defined by User)


Exposure Time(s): *Within Full Well Depth*

Maximum Exposure Time(s)

Results

Photons from Object: Photons from Sky Background: Photons from Telescope:

Exposure Time(s): SN_GivenTime:



Ready to calculate!!



Key performance achieved with current design

- FOV: 0.584 degree^2
- 1σ 25 seconds: 18.5 mags at 235K(-38C)
- 10σ 1 hour: 18.7 mags at 235K(-38C)
- Kdark sky background: $100\mu\text{Jy}/\text{sec}^2$



Where are we now?



	Milestone Completion	Due Date
1	Preliminary discussions with DoS re: ITAR	<i>Jan-15</i>
2	Project Kick-off (Meeting in Hong Kong)	<i>Mar-15</i>
3	Detector & Interface Specification	<i>Jul-15</i>
4	Requirements Review	<i>Aug-15</i>
5	RFQ Teledyne	<i>Aug-15</i>
6	Contract Negotiation (Detector)	<i>Sep-15</i>
7	Purchase Order (Detector)	<i>Oct-15</i>
8	CDR (De-Scope Option)	<i>Dec-15</i>
9	Final Design Review	<i>Apr-16</i>
10	Procurement Lead-time (Detector)	<i>Nov-16</i>
11	Telescope shipped to Australia	<i>Dec-16</i>
12	Float Procurement Lead-time (Detector)	<i>Jan-17</i>
13	AIT @ AAO Facility (location TBD)	<i>Feb. – June</i>
<i>N/A</i>	<i>Schedule Float</i>	<i>~4 months</i>
14	Camera Pre Delivery Review	<i>Late 2017</i>
15	Shipping to Antarctica	<i>Nov. 2017</i>
16	Commissioning	<i>Jan. 2018</i>
17	Science Survey commences	<i>Feb. 2018</i>

